

# SAFETY DATA SHEET

## HYDRATED LIME

### SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** Hydrated Lime  
**Synonym/s:** HY, High Calcium Hydrated Lime, Hydrate, Slaked Lime, HL  
**Chemical Name:** Calcium Hydroxide  
**Chemical Formula:** Ca(OH)<sub>2</sub>  
**Product Use/s:** Water Treatment, pH Adjustment, FGD, Construction, Pulp/Paper

**Manufacturer:** Cheney Lime and Cement Company  
478 Graystone Road  
Allgood, Alabama 35013  
205-625-3031

**Emergency Phone:** 205-625-3031

### SECTION 2: HAZARDS IDENTIFICATION

**Emergency Overview:** Hydrated Lime is an odorless white powder. Contact can cause irritation to eyes, skin, respiratory system, and gastrointestinal tract.

**Hazard Pictograms:**



**Signal Word:**

Danger

**Potential Health Effects:**

**Eyes:** Contact can cause severe irritation or burning of eyes, including permanent damage.

**Skin:** Contact can cause severe irritation or burning of skin, especially in the presence of moisture.

**Ingestion:** This product can cause severe irritation or burning of gastrointestinal tract if swallowed.

**Inhalation:** This product can cause severe irritation of the respiratory system. Long-term exposure may cause permanent damage. Hydrated lime is not listed by MSHA, OSHA, or IARC as a carcinogen. However, this product may contain trace amounts of crystalline silica in the form of quartz or cristobalite, which has been classified by IARC as a Group I carcinogen to humans when inhaled. Inhalation of silica can also cause a chronic lung disorder, silicosis.

**Potential Environmental Effects:**

This material is alkaline and if released into water or moist soil will cause an increase in pH.

# SAFETY DATA SHEET

## HYDRATED LIME

### SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	Chemical Formula	Common Name	Conc. (%)
Calcium Hydroxide	Ca(OH) <sub>2</sub>	Hydrated Lime	> 90
Magnesium Oxide	MgO	Periclase	< 2.5
Calcium Carbonate	CaCO <sub>3</sub>	Limestone	< 3.0
Crystalline Silica	SiO <sub>2</sub>	Quartz	< 1.0

### SECTION 4: FIRST AID MEASURES

**Eyes:** Immediately flush eyes with generous amounts of water or eye wash solution if water is unavailable. Pull back eyelid while flushing to ensure that all hydrated lime dust has been washed out. Seek medical attention promptly if the initial flushing of the eyes does not remove the irritant. Do not rub eyes.

**Skin:** Brush off or remove as much dry lime as possible. Wash exposed area with large amounts of water. If burned seriously or if irritation persists, seek medical attention promptly.

**Inhalation:** Move victim to fresh air. Seek medical attention. If breathing has stopped, give artificial respiration.

**Ingestion:** Do not induce vomiting. Seek medical attention immediately. Never give anything by mouth unless instructed to do so by medical personnel.

**Medical Conditions Aggravated by Exposure:** Hydrated lime is an odorless white powder. Contact can cause irritation to eyes, skin, respiratory system, and gastrointestinal tract.

### SECTION 5: FIREFIGHTING MEASURES

#### Fire Hazards:

**Suitable Extinguishing Media:** Use dry chemical or CO<sub>2</sub> fire extinguisher to extinguish the surrounding fire.

**Fire Fighting Instructions:** Keep personnel away from and upwind of fire. Avoid skin contact or inhalation of dust. Wear full fire-fighting turn-out gear (full Bulk gear), and respiratory protection (SCBA)

**Hazardous Combustion Products:** Not applicable

# SAFETY DATA SHEET

## HYDRATED LIME

### SECTION 6: ACCIDENTAL RELEASE MEASURES

**Spill / Leak Procedures:** Do Not use water on bulk material spills. Use proper personal protective equipment.

**Small Spills:** Use dry methods to collect spilled materials. Avoid generating dust. Do not clean up with compressed air. Store collected materials in dry, sealed plastic or non-aluminum metal containers. Residue on surfaces may be water washed.

**Large Spills:** Use dry methods to collect spilled materials. Evacuate area downwind of clean-up operations to minimize dust exposure. Store spilled materials in dry, sealed plastic or non-aluminum metal containers.

**Containment:** Minimize dust generation and prevent bulk release to sewers or waterways.

**Clean-up:** Residual amounts of material can be flushed with large amounts of water. Equipment can be washed with either a mild vinegar and water solution, or detergent and water.

### SECTION 7: HANDLING AND STORAGE

**Handling:** Keep in tightly closed plastic or non-aluminum metal containers. Protect containers from physical damage. Avoid direct skin contact with the material. Avoid breathing any dust.

**Storage:** Store in a cool, dry, well-ventilated location. Do not store near acids or other incompatible materials. Keep away from moisture. Do not store or ship in aluminum containers. Hydrated lime is not combustible or flammable. However, it reacts vigorously with acids, and may release heat sufficient to ignite combustible materials in specific instances. Hydrated lime is not considered to be an explosion hazard, although reaction with acids or other incompatible materials may rupture containers.

### SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Ingredient	OSHA PEL, TWA 8/40h (mg/m3)	ACGIH TLV, TWA 8/40h (mg/m3)	NIOSH REL,TWA 8/40h (mg/m3)	NIOSH IDLH (mg/m3)
Calcium Hydroxide	15 (total dust) 5 (respirable)	5	5	N/A
Magnesium Oxide	10	10	N/A	N/A
Calcium Carbonate	15 (total dust) 5 (respirable)	10	10(total dust) 5 (total dust)	N/A
Crystalline Silica	10/(SiO <sub>2</sub> % + 2) (respirable)	0.025 (respirable)	0.05 (respirable)	50

# SAFETY DATA SHEET

## HYDRATED LIME

**Engineering Controls:** Provide ventilation adequate to maintain PELs.

**Respiratory Protection:** Use NIOSH/MSHA approved respirators if airborne concentration exceeds PELs.

**Skin Protection:** Use appropriate gloves and footwear to prevent skin contact and the potential for burns. Clothing should fully cover arms and legs. Should lime get inside clothing or gloves, remove the clothing and the lime promptly.

**Eye Protection:** Use safety glasses with side shields or safety goggles. Contact lenses should not be worn when working with lime products.

**Other:** Eye wash fountain/stations and emergency showers should be available.

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance:</b>	White free flowing powder
<b>Odor:</b>	Odorless
<b>Physical State:</b>	Solid
<b>Melting Point (°C/°F):</b>	decomposes at 580/1076
<b>Boiling Point (°C/°F):</b>	N/A
<b>Bulk Density:</b>	25-35 lbs. /cu. Ft.
<b>Specific Gravity:</b>	2.3 – 2.4
<b>Vapor Pressure (mm Hg):</b>	N/A
<b>Vapor Density:</b>	N/A
<b>Evaporation Rate:</b>	N/A
<b>pH (25°C/77°F):</b>	12.4
<b>Solubility in Water:</b>	0.159 grams per 100 grams sat. sol. at 25°C

### SECTION 10: STABILITY AND REACTIVITY

**Stability:** Chemically stable, but slowly reacts with CO<sub>2</sub> to form calcium carbonate.

(See also Incompatibility below.)

**Hazardous Decomposition/Products:** Does not occur

**Hazardous Polymerization:** Does not occur

**Incompatibility/Conditions to Avoid:**

Hydrated lime should not be mixed or stored with the following materials, due to the potential for vigorous reaction and release of heat:

Acids (unless in a controlled process), Organic Acid Anhydrides, Reactive Fluoridated Compounds, Nitro-Reactive Brominated Compounds, Reactive Phosphorous Compounds, Reactive Powdered Metals, Interhalogenated Compounds

# SAFETY DATA SHEET

## HYDRATED LIME

### SECTION 11: TOXICOLOGICAL INFORMATION

ORL-RAT LD50: 7,340 mg/kg ORL-MUS LD50: 7,300 mg/kg

Hydrated lime is not listed by MSHA, OSHA, or IARC as a carcinogen, but this product may contain trace amounts of crystalline silica, which has been classified by IARC as carcinogenic to humans when inhaled in the form of quartz or cristobalite. Inhalation, skin and eye contact are the most likely routes of exposure. This material is irritating to the skin and severely irritating to the eyes.

### SECTION 12: ECOLOGICAL INFORMATION

**Eco-toxicity:** Because of the high pH of this product, it would be expected to produce significant Eco-toxicity upon exposure to aquatic organisms and aquatic systems in high concentrations (> 1 g/L).

**Environmental Fate:** This material shows no bioaccumulation effect or food chain concentration toxicity. High pH values will rapidly decrease over time as a result of recarbonation. This material may be used in soil stabilization or remediation and will show very little mobility in soils.

### SECTION 13: DISPOSAL CONSIDERATIONS

Dispose of in accordance with all applicable federal, state, and local environmental regulations. If this product as supplied, and unmixed, becomes a waste, it will not meet the criteria of a hazardous waste as defined under the U.S. Resource Conservation and Recovery Act (RCRA).

### SECTION 14: TRANSPORTATION INFORMATION

Hydrated lime is not classified as a hazardous material by US DOT and is not regulated by the Transportation of Dangerous Goods (TDG) when shipped by any mode of transport.

### SECTION 15: REGULATORY INFORMATION

#### U.S. EPA Regulations:

RCRA Hazardous Waste Number (40 CFR 261.33): **not listed**

RCRA Hazardous Waste Classification (40 CFR 261): **not classified**

CERCLA Hazardous Substance (40 CFR 302.4) **unlisted specific per RCRA, Sec. 3001;**

CWA, Sec. 311(b)(4); CWA, Sec. 307(a), CAA, Sec. 112

CERCLA Reportable Quantity (RQ), **not listed**

SARA 311/312 Codes: **not listed**

SARA Toxic Chemical (40 CFR 372.65): **not listed**

SARA EHS (Extremely Hazardous Substance) (40 CFR 355): **not listed**

Threshold Planning Quantity (TPQ): **not listed**

All chemical ingredients are listed on the US EPA TSCA Inventory List.

# SAFETY DATA SHEET

## HYDRATED LIME

### OSHA/MSHA Regulations:

Air Contaminant (29 CFR 1910.1000, Table Z-1, Z-1-A): 5mg/M3 TWA-8

MSHA: **not listed**

OSHA Specifically Regulated Substance (29 CFR 1910): **not listed**

State Regulations: Consult state and local authorities for guidance. Components found in this product may contain trace amounts of inherent naturally occurring elements (such as, but not limited to arsenic and cadmium) that may be regulated under California Proposition 65 and other states regulations.

### Canada:

WHMIS Classification: "D2A" Materials Causing Other Toxic Effects

WHMIS Classification: "E" Corrosive Materials (listed due to corrosive effect on aluminum)

Canada DSL: **Listed**

### SECTION 16: OTHER INFORMATION

Prepared By: Cheney Lime and Cement Company

Date Prepared: June 1, 2015

NFPA Hazard Class: Health: 2 Flammability: 0 Instability: 0

HMIS Hazard Class: Health: 2\* Flammability: 0

**Physical Hazard: 0**

**Personal Protection: E**

**Abbreviations:** N/A - Not Applicable, IARC - International Agency for Research on Cancer, IATA - International Air Transport Association, ACGIH - American Conference of Governmental Industrial Hygienists, TWA - Time Weighted Average, PEL - Permissible Exposure Limit, TLV - Threshold Limit Value REL Recommended Exposure Limit.

Cheney lime and Cement Company provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person. Individuals receiving this information must consult their own technical and legal advisors and/ or exercise their own judgment in determining its appropriateness for a particular purpose.

Cheney Lime and Cement Company makes no representations or warranties, either express or implied, including without limitation and warranties of merchantability or fitness for a particular purpose with respect to the information set forth herein or the product(s) to which the information refers. Accordingly, Cheney Lime And Cement Company will not be responsible or liable for any claims, losses or damages resulting from the use of or reliance upon or failure to use this information.

Revision: 02

Visit <http://www.cheneylime.com> for the latest SDS versions